
























RM SERIES SPECIFICATION

MACHINE TYPE [RM]	300	600	1000	1800	2500	3500	4500
Total capacity [L]	300	600	1000	1800	2500	3500	4500
Max filling [L]	225	450	750	1350	1875	2625	3375
Motor power [kW]	5,5	7,5	11	15	22	30	37
Shaft rotation speed [rpm]	4-36	3-28	3-22	3-18	3-15	2-12	1-10
Standard control							
Mixer net weight [kg]	640	940	1550	1900	2600	3400	4200
Fuse [A]	25	32	50	63	100	120	140
Loader option	PW 2/250	PW 2/250	PW 2/250	PW 2/250	PZ 2/250 or PW 2/1000	PZ 2/250 or PW 2/1000	PZ 2/250 or PW 2/1000
Unloading bin DIN 9797	200L 	200L 	200L 	200L 	1x200L 	1x200L 	1x200L 
Opening/Closing lids							

MODEL OF MACHINES [RM]	300	600	1000	1800	2500	3500	4500
Column loader	o	o	o	o	o	o	o
PLC and HMI	S	S	S	S	S	S	S
Smooth variable speed	S	S	S	S	S	S	S
Temperature sensor	o	o	o	o	o	o	o
Water dosing system	o	o	o	o	o	o	o
Weighing system	o	o	o	o	o	o	o
"Easy Clean" shafts seals	-	-	-	-	-	-	-
Additional grid	o	o	o	o	o	o	o
Polished shafts and bath	o	o	o	o	o	o	o
Double jacket max pressure 2.0 Bar	o	o	o	o	o	o	o
Dust proof sealed lid	S	S	S	S	S	S	S
Vacuum version	o	o	o	o	o	o	o

RM SERIES SPECIFICATION



MODEL OF MACHINES [RM]	300	600	1000	1800	2500	3500	4500
H [cm]	180	188	210	243	251	273	296
H1 [cm]	156	167	190	210	220	232	244
H2 [cm]	280	311	280	310	350	375	398
H3 [cm]	282	282	300	325	341	361	378
L [cm]	200	218	260	295	303	385	418
L1 [cm]	223	232	287	330	339	420	453
A [cm]	80	88	102	124	138	154	167
A1 [cm]	160	170	180	201	215	231	238